## GOVT ITI MALERKOTLA TOOL & EQUMENT TARDE: PLUMBER

| _     | 100L &                                  | EQUAVIT         | INI IARDE. I LUN  | A.   |
|-------|---|-----------------|---|--|
| s.no. | NAME OF THE ITEM                        | STD LIST<br>NO. | SPECIFICATION   | I  |
| 1     | Marking table 900<br>*600*900mm height  | B-2             | 900*600*900mm height  |  |
| 2     | V block with clamps<br>80/7-63a is 2949 | B-3             | V block with clamps 80/7-63a is 2949  |  |
| 3     | Combination set 200mm                   | B-4             | 200mm   |  |
| 4     | Screw pitch gauge to cover above thread | B-19            | Screw pitch gauge to cover above thread 10 blade  |  |
| 5     | Stove melting solder                    | B-24            | Stove melting solder standard size  |  |
| 6     | Snip bend 250mm                         | B-29            | 250mm HCS   |  |
| 7     | Scribing gauge                          | B-48            | 200mm   |  |
| 8     | Bending spring                          | B-53            | Standard size   |  |
| 9     | Hammering drill machine                 | B-103           | Hammering drill m/c<br>20mm,230v/50hz 580,0-<br>850pm,2.6a 2.2kgs,drill<br>size steel 10mm,wood<br>30mm concrete 20mm   | And the second s |
| 10    | Ring guage<br>15mm,20mm,25mm,32<br>mm   | B-100           | 15mm,20mm,25mm,32mm   |  |
| 11    | Solar water heater system               | B-99            | Capacity 100lt. Temperature of solar system is up to 60degree C. The of tubes are ten in numbers. The water Circulation from tank to SWHS and vice versa to the washrooms through gravity. The heater is 2kw tank is of stainless steel with 1mm thick and 50mm put insulation with capacity 100lt. collector area is 1.5 meter per 100 ltr. The hot & cold water pipe line extra provided by customer. |  |